ASUS BE248QF
Business Monitor

Accessory slot for phone holder

PC mounted via mini PC kit

Key Features

IPS Ultra-wide Viewing Angles — Optimized for the finest image and color quality with 178° wide-viewing-angle

100Hz — 100Hz refresh rate gives you so much more on top of the best smooth and quality for any content

HDMI HIGH DEFINITION MULTIMEDIA INTERFACE / **DisplayPort** — Extensive connectivity of USB-C, HDMI, DP, USB hub and earphone jack

USB Hub — Embedded USB3.2 Gen 1 type A ports for connecting mouse, keyboard, or other USB devices

4-way Ergonomic Stand — Ergonomically-designed stand with tilt, swivel (+180° ~ -180°), pivot, and height adjustments

Wall Mountable — Space saving from compatible VESA mount standard (100 x 100 mm) and bundled ASUS miniPC kit(optional)

Flicker-free — To eliminate the disturbing flickers on screen to reduce eye fatigue

Ultra-low Blue Light — Adjustable Ultra-low Blue Light for your best viewing experience

Stereo Speaker — Built-in stereo speakers for audio experience

ENERGY STAR

TCO CERTIFIED

epeat GOLD (By country)

TÜVRheinland CERTIFIED

FSC www.fsc.org FSC® N004058 The mark of responsible forestry

ASUS

Specification

Display	Panel Size(diagonal)	24.1"(61.13 cm) Wide Screen (16:10)
	Display Viewing Area(HxV)	518.4 x 324.0 mm
	Panel Type	IPS
	Display Surface	non-glare
	Color Saturation	100% sRGB
	True Resolution	1920x1200
	Pixel Pitch	0.270mm
	Brightness (Max.)	350cd/m²
	Contrast Ratio (Max.)	3000:1
	Viewing Angle (CR≧10)	178°(H)/178°(V)
	Display Colors	16.7 million
	Response Time	5ms (GTG)
	Refresh Rate (Max)	100Hz
	HDR (High Dynamic Range) Support	HDR10
	Flicker-free	Yes
Video Features	Splendid™ Video Intelligence Tech.	Yes
	Skin-Tone Selection	3 modes
	Color Temperature Selection	4 modes (Cool/Normal/Warm/User)
	HDCP support	Yes (ver. 1.4)
	QuickFit	Yes
	Blue Light Filter	Yes
	VRR Technology	Yes (Adaptive-Sync)
	DisplayWidget	Yes, DisplayWidget Center
Audio Features		Stereo Speaker 2W x 2
Input/ Output		HDMI, DP, D-Sub, USB3.2 Gen1 x4 ports (downstream), Earphone jack, PC Audio Input
Signal Frequency	Digital Signal Frequency	TBA
Power	Power Consumption*1	TBA
	Power Saving Mode	<0.5W
	Power Off Mode	0W(hard switch)
	Voltage	100−240V, 50 / 60 Hz
Mechanical Design	Color	Black
	Tilt(angle)	Yes (+35° ~ -5°)
	Swivel(angle)	Yes (+180° ~ -180°)
	Pivot(angle/direction)	Yes (+90° ~ -90°)
	Height Adjustment	Yes (0~130mm)
	VESA Wall Mounting	100x100mm
Security	Kensington lock	Yes
Dimension	Phys. Dimension (WxHxD)	53.18 x 47.31 x 21.12 cm (20.94" x 18.63" x 8.31") (with stand), 53.18 x 35.00 x 4.00 cm (20.94" x 13.78" x 1.57") (without stand)
	Box Dimension (WxHxD)	61.0 x 41.4 x 14.00 cm (24.02" x 16.30" x 5.51")
Weight		Net Weight : 5.5 kg (12.13 lbs) Net Weight without Stand : 3.75 kg (8.27 lbs) Gross Weight : 8.2 kg (18.08 lbs)
Accessories(vary by regions)		Power cord(1.8m), HDMI cable(1.8m), DisplayPort Cable(optional), Warranty card, Quick Start Guide, mini PC kit(optional), USB 3.2 cable
Compliance Standards		FCC, UL/cUL, ICES-3, CB, CE, ErP, WEEE, TUV-GS, TUV-Ergo, ISO 9241-307, UkrSEPRO, CU, CCC, CEL, CECP, BSMI, RCM, AU MEPS, VCCI, PSE, PC Recycle, J-MOSS, KC, KCC, KMEPS, Energy Star, TCO, RoHS, CEC, WHQL Windows 10/11, EPEAT Gold(by country), TUV Flicker free, TUV Low Blue Light

*1.Measuring a screen brightness of 200 nits without audio/ USB/ Card reader connection
*.All specifications are subject to change without notice.

ASUS