

HARDWARE-FUNKTIONEN

Schnittstelle	Uplink: 10/100/1000 Mbps Ethernet Port*1 Downlink: 10/100/1000 Mbps Ethernet Port*1
Physischer Diebstahlschutz	No
Taste	LED/Wi-Fi Button, RESET
Spannungsversorgung	802.3af/802.3at PoE
Energieverbrauch	9 watts /25.5 watts (PoE Out Included)
Dimensions	143 × 86 × 19.7mm (5.6 × 3.4 × 0.8 in)
Antenne	2 Dual-Band Antennas 2.4GHz: 2*4 dBi 5GHz: 2*3.6 dBi
Montage	Wall Plate Mounting
Hardware Watch Dog	Yes

WLAN-FUNKTIONEN

WLAN-Standards	IEEE 802.11n/g/b/ac
Frequenz	2.4GHz and 5GHz
Signalrate	5GHz: Up to 867Mbps 2.4GHz: Up to 300Mbps
WLAN-Funktionen	16 SSIDs (Up to 8 SSIDs on each band) Enable/Disable Wireless Radio Automatic Channel Assignment Transmit Power Control (Adjust Transmit Power on dBm) QoS(WMM) Load Balance Rate Limit Reboot Schedule Wireless Schedule Wireless Statistics based on SSID/AP/Client Captive Portal Authentication Access Control Wireless Mac Address Filtering Wireless Isolation Between Clients
WLAN-Sicherheit	SSID to VLAN Mapping Local LAN port based VLAN Rogue AP Detection 802.1X Support 64/128/152-bit WEP / WPA / WPA2-Enterprise, WPA-PSK / WPA2-PSK
Sendeleistung	CE: ≤20 dBm (2.4 GHz, EIRP) ≤23 dBm (5 GHz, EIRP) FCC: ≤21 dBm (2.4 GHz) ≤21 dBm (5 GHz)

VERWALTUNG

Omada Cloud Access	Yes
Omada App	Yes
Omada Cloud Controller	Yes
Centralized Management	<ul style="list-style-type: none">• Omada Cloud-Based Controller• Omada Hardware Controller (OC300)• Omada Hardware Controller (OC200)• Omada Software Controller

VERWALTUNG

Omada Controller Software	Yes
Cloud Access	Yes (Through OC300, OC200, Omada Cloud-Based Controller, or Omada Software Controller)
Benachrichtigung per E-Mail	Yes
LED abschaltbar	Yes
Managementzugriff MAC-Adress-basiert filterbar	Yes
SNMP	v1,v2c
Lokales/Remote-Systemprotokoll	Local/Remote Syslog
SSH	Yes
Weboberfläche	HTTP/HTTPS
Layer3-Management	Yes
Multi-Site-Management	Yes
Management VLAN	Yes

SONSTIGES

Zertifizierung	CE, FCC, RoHS Omada AC1200 Wireless MU-MIMO Wall-Plate Access Point
Verpackungsinhalt	EAP225-Wall Installation Guide Mounting Screw
Systemanforderungen	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10
Umgebung	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing