

16/24 Port Gigabit Easy Smart PoE+ Switch

MODEL: TL-SG1218MPE / TL-SG1428PE



Highlights

- 16 PoE+ Gigabit RJ45 ports, 2 Gigabit RJ45 ports and 2 combo Gigabit SFP slots (For TL-SG1218MPE) / 24 PoE+ Gigabit RJ45 ports, 2 Gigabit RJ45 ports and 2 Gigabit SFP slots (For TL-SG1428PE)
- High PoE power budget with up to 30 W for each PoE port and 250 W* for all PoE ports
- Working with IEEE 802.3af/at compliant PDs
- PoE Auto Recovery automatically reboots your dropped or unresponsive PoE-powered devices
- Advanced Features for higher performance like 802.1Q VLAN, 802.1p QoS and IGMP Snooping
- Intelligent power management module like PoE Schedule, PoE Priority, PoE Power Limit
- Easy to Use, the web-based UI and management utility simplify the configuration

Overview

TL-SG1218MPE / TL-SG1428PE with 16/24 ports supporting the PoE+ standard provides a simple way to expand the wired network while transferring power over the same ethernet cable at the same time. With a total power budget of 250 W*, up to 30 W per port, and the powerful PoE Module, TL-SG1218MPE / TL-SG1428PE can power more high-powered devices such as Access Points, IP Cameras, IP Phones. Moreover, TL-SG1218MPE / TL-SG1428PE can provide 802.1q VLAN, IGMP Snooping, LAG and other software functions to meet various network configuration needs.

Power over Ethernet for Simplified Network Deployment

- Features 16 (For TL-SG1218MPE) / 24 (For TL-SG1428PE) 802.3af/at compliant PoE+ ports, with a total PoE power budget of 250 W*
- Flexible deployment for PoE supported devices such as wireless access points (APs), IP phones, and IP cameras
- Designed to use a single Ethernet cable for both data and power transmission, lowering infrastructure costs

Highlight Performance


- Advanced feature - QoS optimizes the performance of quality-sensitive application like Surveillance Video. And IGMP Snooping ensures the multicast stream be forwarded intelligently to the appropriate subscribers by the switch.
- After configuring the PoE management module, TL-SG1218MPE / TL-SG1428PE can control the Power Limit, Port Priority, and PoE Scheduling of each PoE port.
- PoE Auto Recovery automatically reboots your dropped or unresponsive PoE-powered devices.

Easy to Use

- Plug & play, no configuration required
- Auto MDI/MDIX eliminates the need for crossover cables
- Auto-negotiation intelligently adjusts for compatibility and optimal performance

Specifications

Hardware Features & Performance

Product Picture			
Model		TL-SG1218MPE	TL-SG1428PE
General	Interfaces	18 10/100/1000Mbps RJ45 Ports 2 Gigabit Combo SFP Slots	26 10/100/1000Mbps RJ45 Ports 2 Gigabit SFP Slots
PoE	PoE Standard	802.3 af/at	802.3 af/at
	PoE Ports	16, up to 30 W Per Port	24, up to 30 W Per Port
	PoE Power Budget	250 W*	250 W*
Performance	Switching Capacity	36 Gbps	56 Gbps
	Packet Forwarding Rate	26.78 Mpps	41.66 Mpps
	Max Address Table	8 K	8 K
	Packet Buffer	4.1 Mbit	4.1 Mbit
	Jumbo Frame	10 KB	10 KB
Physical & Environment	Power Supply	100-240V AC, 50/60Hz	100-240V AC, 50/60Hz
	Maximum Power Consumption (220V/50Hz)	19.4 W (220V/50Hz, no PD connected) 293.3 W (220V/50Hz, with 250W PD connected)	25.5 W (220V/50Hz, no PD connected) 299.2 W (220V/50Hz, with 250W PD connected)
	Maximum Heat Dissipation	66.15 BTU/h (no PD connected) 1000.15 BTU/h (with 250 W PD connected)	86.96 BTU/h (no PD connected) 1020.27 BTU/h (with 250 W PD connected)
	Dimensions (W×D×H)	17.3 × 7.1 × 1.7 in. (440 × 180 × 44 mm)	17.3 × 8.7 × 1.7 in. (440 × 220 × 44 mm)
	FAN Quantity	2	2
	Operating Temperature	0°C~50°C (32°F~122°F)	0°C~50°C (32°F~122°F)
	Storage Temperature	-40°C~70°C (-40°F~158°F)	-40°C~70°C (-40°F~158°F)
	Operating Humidity	10%~90%RH, non-condensing	10%~90%RH, non-condensing
	Storage Humidity	5%~90%RH, non-condensing	5%~90%RH, non-condensing
Certification	CE, FCC	CE, FCC	

Software Features

L2 Features	<ul style="list-style-type: none"> • Link Aggregation <ul style="list-style-type: none"> - Static link aggregation - Up to 8 aggregation groups and up to 4 ports per group • Loopback Detection • Port Statistics • Cable Test • Flow Control • Mirroring <ul style="list-style-type: none"> - Port Mirroring - Ingress/Egress/Both
IGMP Snooping	<ul style="list-style-type: none"> • IGMP v1/v2/v3 Snooping • 128 Max Multicast Entries
VLAN	<ul style="list-style-type: none"> • 802.1Q VLAN • Port Based VLAN • MTU VLAN
QoS	<ul style="list-style-type: none"> • Port Based, 802.1p Based, 802.1p QoS/ DSCP priority • Bandwidth Control <ul style="list-style-type: none"> - Ingress Rate/Egress Rate/Both • Storm Control <ul style="list-style-type: none"> - Broadcast/Multicast/Unknown-Unicast Control
PoE	<ul style="list-style-type: none"> • PoE Management • PoE Auto Recovery • Extend Mode

* PoE budget calculations are based on laboratory testing. Actual PoE power budget is not guaranteed and will vary as a result of client limitations and environmental factors.

Some models featured in this guide may be unavailable in your country or region. Visit TP-Link website for local sales information: www.tp-link.com.

www.tp-link.com

Specifications are subject to change without notice. All brands and product names are trademarks or registered trademarks of their respective holders. © 2023 TP-Link